

PS4000 C-SJ5-25

Solar Submersible Pump System for 4" wells

System Overview

Head	max. 140 m
Flow rate	max. 7.0 m³/h

Technical Data

Controller PS4000

- Control inputs for dry running protection, remote control etc.
- Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracking)

Power	max. 4.0 kW
Input voltage	max. 375 V
Optimum Vmp*	> 238 V
Motor current	max. 15 A
Efficiency	max. 98 %
Ambient temp.	-30...50 °C
Enclosure class	IP54

Motor ECDRIVE 4000-C

- Maintenance-free brushless DC motor
- Water filled
- Premium materials, stainless steel: AISI 304/316
- No electronics in the motor

Rated power	3.5 kW
Efficiency	max. 92 %
Motor speed	900...3 300 rpm
Insulation class	F
Enclosure class	IP68
Submersion	max. 250 m


Pump End PE C-SJ5-25

- Non-return valve
- Premium materials, stainless steel: AISI 304

Pump Unit PU C-SJ5-25 (Motor, Pump End)

Borehole diameter	min. 4,0 in
Water temperature	max. 50 °C

Standards



IEC/EN 61702:1995,
IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature




PS4000 C-SJ5-25

Solar Submersible Pump System for 4" wells

Pump Chart


Vmp* > 238 V



Dimensions and Weights


Controller

- H = 595 mm
- H2 = 563 mm
- W1 = 178 mm
- W2 = 156 mm
- W3 = 116 mm
- D = 165 mm
- D1 = 150 mm



Pump Unit

- A = 941 mm
- B = 245 mm
- C = 696 mm
- D = 96 mm
- E = 98 mm
- S = 1.5 in



	Net weight
Controller	9.0 kg
Pump Unit	18 kg
Motor	10 kg
Pump End	8.0 kg

*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

